

Owner's Manual with Installation Instructions

Banks A-Pillar Single Gauge

2009-2014 Ford F-150

THIS MANUAL IS FOR USE WITH SYSTEM 63206, 63207

Gale Banks Engineering
546 Duggan Avenue • Azusa, CA 91702
(626) 969-9600 • Fax (626) 334-1743

Product Information & Sales: (888) 635-4565
Customer Support: (888) 839-5600
Installation Support: (888) 839-2700

bankspower.com

A large, stylized, grey version of the "banks" logo, tilted at an angle, positioned in the bottom right corner of the page.

General Installation Practices

Dear Customer,

If you have any questions concerning the installation of your Banks A-Pillar Mount System, please call our Technical Service Hotline at (888) 839-2700 between 7:00 am and 4:00 pm (PT). Watching our how-to video (link on the cover) may alleviate any further questions. If you have any questions relating to shipping or billing, please contact our Customer Service Department at (888) 839-5600.

Thank you.

1. Before starting work, familiarize yourself with the installation procedure by reading all of the instructions.
2. Throughout this manual, the left side of the vehicle refers to the driver's side, and the right side to the passenger's side.
3. Disconnect the negative (ground) cable from the battery (or batteries, if there are two) before beginning work.

Tools Required:

- Phillips head screwdriver

63206-01



What's Included

Item #	Description	Part #	QTY
1	Pillar Mount Kit, Single Gauge	63206-01	1
2	Owner's Manual	96417	1

A-Pillar Mount Installation

1. Remove side dash panel. If the vehicle has a speaker on stock pillar, disconnect speaker harness. See **Step 1**.



2. Remove stock pillar by starting at the top and pulling towards the driver seat, while sliding up towards the headliner. This will release the two securing tabs from the dash. See **Step 2**.



3. For speaker models, reinstall speaker onto Banks Pillar. Prep for Banks Pillar install by partially threading the supplied screw into the supplied well nut. Slide the well nut onto the upper slot, and then remove the screw, leaving the well nut in place. See **Step 3**.



4. Run the applicable iDash wiring up through the stock pillar location in preparation for the Banks Pillar. For speaker models, reconnect speaker harness. Begin install by aligning the securing tabs with the slots in the dash. See **Step 4**.



5. Connect iDash before fully installing Banks Pillar. Insert screw into upper hole on the Banks Pillar and align with the previously inserted well nut. Finish install by tightening screw, but taking care to not overtighten. See **Step 5**.



6. Ensure Banks Pillar is fully installed by making sure it sits below both the dash where the tabs were inserted, and behind the weather stripping along the pillar itself. See **Step 6**.



Gale Banks Engineering
546 Duggan Avenue • Azusa, CA 91702
(626) 969-9600 • Fax (626) 334-1743

Product Information & Sales: (888) 635-4565
Customer Support: (888) 839-5600
Installation Support: (888) 839-2700

bankspower.com